## IN THE CLAIMS

Kindly replace the present claims by the following set of claims:

- 1. (Cancelled)
- (Currently amended) A method of communicating betweenwith an electronic device andhaving a computer, the method comprising:

providing said computer having-with an audible sound receiving and generating subsystem including a microphone and a loudspeaker;

transmitting from the electronic devicea-source at least one first acoustic signal, encoded with information, to said computer;

receiving said at least one first acoustic signal by said microphone, to be detected by said computer;

processing said at least one first acoustic signal to extract said encoded information; and transmitting to said electronic devicesource, using said loudspeaker, at least a second acoustic signal, encoded with information, in response to said detected at least one first acoustic signal.

- (Previously presented) A method according to claim 2, wherein at least one of said at least one first acoustic signal and at least a second acoustic signal comprises an ultrasonic signal.
- 4-7. (Cancelled)
- 8. (Previously presented) A method of communicating with an electronic device having a computer, the method comprising:

providing said computer having a sound receiving and generating sub-system including a microphone;

transmitting from a source at least one acoustic signal, encoded with information to said computer;

receiving said at least one acoustic signal by said microphone; and

forwarding an indication of said encoded information to a remote computer, over an Internet.

wherein said at least one acoustic signal comprises a stand alone signal not overlaid on a human tangible signal.

- 9. (Original) A method according to claim 8, wherein said indication comprises a sound file.
- 10. (Original) A method according to claim 8, wherein said indication comprises a data file.
- 11. (Previously presented) A method according to claim 8, wherein said acoustic signal comprises an ultrasonic signal.
- 12. (Previously presented) A method according to claim 2, wherein said computer comprises a PDA, personal digital assistant.
- 13. (Previously presented) A method according to claim 2, wherein said computer comprises a portable computer.
- 14. (Previously presented) A method according to claim 2, wherein said computer comprises a desk-top computer.
- 15-16. (Cancelled)
- 17. (Currently amended) A method according to claim 2, wherein said processing comprises determining a distance between said microphone and said source-electronic device.
- 18. (Currently amended) A method according to claim 2, wherein said processing comprises determining movement of said microphone relative to said sourceelectronic device.

- (Original) A method according to claim 18 wherein said movement comprises angular movement.
- 20. (Original) A method according to claim 18, wherein said movement comprises translation.
- 21. (Currently amended) A method according to claim 2, wherein said processing comprises determining a spatial position of said microphone relative to said sourceelectronic device.
- 22. (Original) A method according to claim 21, wherein said spatial position is a onedimensional spatial position.
- 23. (Original) A method according to claim 21, wherein said spatial position is a twodimensional spatial position.
- 24. (Original) A method according to claim 21, wherein said spatial position is a threedimensional spatial position.
- 25-26. (Cancelled)
- 27. (Previously presented) A method according to claim 2, comprising controlling at least one action of a toy, responsive to said received at least one sound.
- 28-33. (Cancelled)
- 34. (Currently amended) A method according to claim 2, wherein said source-electronic device comprises a toy.
- 35. (ORIGINAL) A method according to claim 34, wherein said information comprises stored player input.

- (Currently amended) A method according to claim 2, wherein said electronic devicesource comprises a smart card.
- 37. (Currently amended) A method according to claim 2, wherein said sourceelectronic device comprises a wireless communication device.
- (Currently amended) A method according to claim 2, wherein said sourceelectronic device comprises a computer.
- 39. (Currently amended) A method according to claim 2, wherein said sourceelectronic device comprises a computer peripheral.
- 40. (Previously presented) A method according to claim 2, wherein said encoded information comprises personal information.
- (Previously presented) A method according to claim 2, comprising logging into said computer responsive to said at least one first acoustic signal.
- 42. (Cancelled)
- 43 (Previously presented) A method according to claim 2, wherein said acoustic signal comprises human audible sound.
- 44. (Previously presented) A method according to claim 43, wherein said human audible sound has a main frequency over 10kHz.
- 45. (Previously presented) A method according to claim 2, wherein said first acoustic signal has a main frequency which is infra-sonic.
- 46-49. (Cancelled)

- (Previously presented) A method according to claim 2, wherein said audible sound subsystem comprises a sound card.
- 51. (Original) A method according to claim 50, wherein said sound card comprises a SoundBlaster compatible sound card.
- 52. (Previously presented) A method according to claim 2, wherein said sound sub-system is designed for audible sound communication with a human operator.
- 53. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency below 50kHz.
- 54. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency below 35kHz.
- 55. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency below 25kHz.
- 56. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency of about 21kHz.
- 57. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency of about 20kHz.
- 58. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency of about 19kHz.
- 59. (Previously presented) A method according to claim 3, wherein said ultrasonic signal has a main frequency of below 18kHz.

60-145. (Cancelled)

146. (Currently amended) A method according to claim 2, wherein said sourceelectronic device comprises a telephone.

147-148. (Cancelled)

149. (Previously presented) A method according to claim 8, wherein said source comprises a telephone.

150. (Cancelled)

151. (Previously presented) A method according to claim 2, wherein said information comprises e-commerce information.

152-153. (Cancelled)

- 154. (Previously presented) A method according to claim 8, wherein said information comprises e-commerce information.
- 155. (Previously presented) A method according to claim 3, wherein said at least one ultrasonic signal comprises a stand alone signal not overlaid on a human tangible signal.
- 156. (New) A method according to claim 3, wherein the at least one first acoustic signal, is digitally encoded with information.
- 157. (New) A method according to claim 2, comprising responding by the computer to the at least one first acoustic signal, as if the computer received an input from a pointing device or a touch screen.